

HighSpeed USB 3.0 LTO Tape Drive

LT 90H/80H2/70H2

Mac Windows Linux

**World's Only USB Connection LTO
High Speed USB 3.0 LTO Tape Drive**



Function

- High speed data transfer at maximum 300 MB/sec
- Plug and play with USB 3.0 interface
- Hybrid model with USB interface and SAS interface is also available
- Large amounts of LTO capacity
- Support Mac, Windows, Linux

Features

- With USB plug and play connection, enable maintenance without stopping the server
- USB cable clamp prevents unexpected cable disconnection
- Support various use
 - Backup & transfer large amounts of data
 - Archive data in Broadcast/Video/Surveillance camera/Medical
 - Countermeasure for Ransomware by managing data off-line
- UNITEX LTFS3000 software is included
 - No special knowledge and skills are required for data storage to LTO tape
 - Data can be copied to LTO tape by drag & drop

...

Specification High Speed USB 3.0 LTO tape drive

Model	LT90H USB-Windows LT90H USB-MacOSX	LT80H2 USB-Windows LT80H2 USB-MacOSX	LT70H2 USB-Windows LT70H2 USB-MacOSX
Drive Type	LTO-9	LTO-8	LTO-7
Interface	USB 3.0		
Capacity	18 TB native 45 TB komprimiert	12 TB native 30 TB komprimiert	6 TB native 15 TB komprimiert
Native data transfer (max.)	maximal 300 MB/s		
OS Support (LTxxH USB-Windows)	Windows 7 / 8 / 8.1 (x64/x86) Windows 10 (Ver.1607 or later) (x64/x86) / Windows 11(x64) Windows Server 2008 R2 / 2012 / 2012 R2 / 2016 / 2019 (x64)		
OS Support (LTxxH USB-MacOSX)	OS X 10.11 (64bit) / macOS 10.12 / 10.13 / 10.14 / 10.15 (64bit) macOS 11 / macOS 12		
Dimensions W x D x H mm	213 x 370 x 58 Main body only (excluding protruding parts)		
Power Supply	AC 100 ~ 240 V ±10 %, 50/60 Hz		
Power Consumption	55 VA	65 VA	
Weight	4,5 kg		
Operating Environment (No condensation) (max. wet bulb temperature)	Temperature 15° ~ 35° Humidity 20 % ~ 80 % 22° C	Temperature 10° ~ 45° Humidity 20 % ~ 80 % 26° C	
Kit Contents LTxxH USB-Windows	LTO Tape Drive, USB 3.0 cable, Cleaning Cartridge, User Guide (English), UNITEX LTFS3000 software (English)		
Kit Contents LTxxH USB-MacOSX	LTO Tape Drive, USB 3.0 cable, Cleaning Cartridge, User Guide (English), UNITEX LTFS3000 software for MacOSX (English)		
Optional Equipment	LTO Ultrium9 Data Cartridge, USB 3.0 Type-C cable	LTO Ultrium8 Data Cartridge, USB 3.0 Type-C cable	LTO Ultrium7 Data Cartridge, USB 3.0 Type-C cable

...

Specification High Speed USB 3.0 / SAS LTO tape drive

Model	LT90H USB SAS-Windows SAS-MacOSX	LT80H2 USB SAS-Windows SAS-MacOSX	LT70H2 USB SAS-Windows SAS-MacOSX
Drive Type	LTO-9	LTO-8	LTO-7
Interface	USB 3.0 / SAS		
Capacity	18TB native 45TB komprimiert	12TB native 30TB komprimiert	6TB native 15TB komprimiert
Native data transfer (max.)	maximal 300 MB/s		
SAS spec.	12 Gbps: 300 MB/s	6 Gbps: 300 MB/s	
OS Support (LTxxH USB/SAS-Windows)	Windows 7 / 8 / 8.1 (x64/x86) Windows 10 (Ver.1607 or later) (x64/x86) / Windows 11 (x64) Windows Server 2008 R2 / 2012 / 2012 R2 / 2016 / 2019 (x64)		
OS Support (LTxxH USB/SAS-MacOSX)	OS X 10.11 (64bit) / macOS 10.12 / 10.13 / 10.14 / 10.15 (64bit) macOS 11 / macOS 12		
Dimensions W x D x H mm	213 x 370 x 58 Main body only (excluding protruding parts)		
Power Supply	AC 100 ~ 240 V ±10 %, 50/60Hz		
Power Consumption	55 VA	65 VA	
Weight	4,5 kg		
Operating Environment (No condensation) (max. wet bulb temperature)	Temperature 15° ~ 35° C Humidity 20 % ~ 80 % 22° C	Temperature 10° ~ 45° C Humidity 20 % ~ 80 % 26° C	
Kit Contents LTxxH USB-Windows	LTO Tape Drive, USB3.0 cable, Cleaning Cartridge, User Guide (English), UNITEX LTFS3000 software (English)		
Kit Contents LTxxH USB-MacOSX	LTO Tape Drive, USB 3.0 cable, Cleaning Cartridge, User Guide (English), UNITEX LTFS3000 software for MacOSX (English)		
Optional Equipment	SAS board/SAS cable, LTO Ultrium9 Data Cartridge, USB 3.0 Type-C Cable	SAS board/SAS cable, LTO Ultrium8 Data Cartridge, USB 3.0 Type-C Cable	SAS board/SAS cable, LTO Ultrium7 Data Cartridge, USB 3.0 Type-C Cable